



HP Latex 365 Printer

Maximize your versatility with this full-feature, 1.63-m (64-in) HP Latex printer



Water-based HP Latex Technology is unique, delivering a combination of true application versatility, high image quality and high productivity, and a sustainable approach that's better for your operators, your business, and the environment.¹

Expand your applications—beat client expectations

- Print on traditional signage substrates and beyond—up to 1.63 m (64 in)—print textiles with the ink collector²
- Reach new indoor spaces that solvent can't, like healthcare—water-based HP Latex Ink prints are odorless
- Enjoy efficient, automated double-sided banner printing
- Produce sharp, consistent, repeatable image quality with high-efficiency curing, 6 colors, and 1200 dpi

Same day delivery—for highly demanding turnarounds

- High quality at high speeds—31 m² (334 ft²)/hr high-speed outdoor quality with HP OMAS, HP Latex Optimizer³
- Reach production speeds and avoid wait time—prints come out completely dry and ready to finish and deliver
- Gain productivity—reduce time between jobs with continuous printing
- You can minimize damage risk—scratch resistance is comparable to hard-solvent inks on SAV and PVC banner⁴

Keep your running costs low—boost your capacity

- Increase production time and reduce time monitoring the printer—automatic, reliable, low-maintenance printing
- Save time—HP Custom Substrate Profiling and i1 embedded spectrophotometer make ICC profiling automatic⁵
- Maintain high image quality over the life of the printer with user-replaceable HP Thermal Inkjet printheads
- Monitor your printer remotely with the free HP Latex Mobile app⁶

For more information, please visit
hp.com/go/Latex365

Join the community, find tools, and talk to experts.
Visit the HP Latex Knowledge Center at
hp.com/communities/LKC

¹ Based on a comparison of HP Latex Ink technology to competitors with leading market share as of December, 2013 and analysis of published MSDS/SDSs and/or internal evaluation. Performance of specific attributes may vary by competitor and ink technology/formulation.

² Performance may vary depending on media—for more information, see hp.com/go/mediasolutionslocator. For best results, use textiles that do not stretch. The ink collector is required for porous textiles.

³ Banner-quality prints in outdoor (4-pass 4-color) mode.

⁴ Estimates by HP Image Permanence Lab on a range of media. Scratch-resistance comparison based on testing HP Latex Inks and representative hard-solvent inks. Outdoor display permanence tested according to SAE J2527 using HP Latex Inks on a range of media, including HP media; in a vertical display orientation in simulated nominal outdoor display conditions for select high and low climates, including exposure to direct sunlight and water; performance may vary as environmental conditions change. Laminated display permanence using HP Clear Gloss Cast Overlaminate. Results may vary based on specific media performance.

⁵ ICC profiling with the spectrophotometer does not support uncoated textiles and backlits.

⁶ HP Latex Mobile is compatible with Android™ 4.1.2 or later and iOS 7 or later, and requires the printer and the smart phone or tablet to be connected to the Internet.

HP Latex 365 Printer (1.63 m / 64 in)

HP Latex Optimizer

- Achieve high image quality at high productivity
- Interacts with HP Latex Inks to rapidly immobilize pigments on the surface of the print

End-to-end sustainability—a better approach

HP Latex Technology delivers all the certifications that matter to your operators, your business, and the environment.⁷



UL ECOLOGO®



Eco Mark Certification
Number 14142007⁹

Using water-based inks eliminates exposure to inks with hazard warning labels and high solvent concentrations, and simplifies ventilation, storage, and transportation requirements.

HP Latex Inks enable more differentiation—odorless prints go where solvent can't.



UL GREENGUARD GOLD¹⁰

HP is designing end-to-end sustainability into large-format printing. The HP Latex 365 Printer is EPEAT Bronze registered—a designation for reduced environmental impact.¹¹



HP Latex Inks

- Scratch resistance comparable to hard-solvent inks on SAV and PVC banner—you can consider unlaminate use for short-term signage¹²
- Outdoor durability up to 5 years laminated, 3 years unlaminate¹³

HP Latex printheads

- See fine details and smooth transitions with HP 831 Latex Printheads providing 1200 dpi native resolution
- Keep day-one image quality by replacing the printheads yourself in a few minutes, without a service call

High-efficiency curing

- Prints are completely cured and dry inside the printer, and ready for immediate finishing and delivery

Easy maintenance and operation

- Accessible print zone with large window and lights
- Enjoy low-maintenance printing with automatic drop detection and nozzle replacement

HP Optical Media Advance Sensor (OMAS)

- Precise and accurate motion control of media advance between print swaths
- Controls registration automatically including double-sided prints with automated registration across sides¹⁴

⁷ Based on a comparison of HP Latex Ink technology to competitors with leading market share as of December, 2013 and analysis of published MSDS/SDSs and/or internal evaluation. Performance of specific attributes may vary by competitor and ink technology/formulation.

⁸ Applicable to HP Latex Inks. UL ECOLOGO® Certification to UL 2801 demonstrates that an ink meets a range of multi-attribute, lifecycle based criteria related to human health and environmental considerations (see ul.com/EL).

⁹ HP 831 Latex Ink Cartridges, certification number 14142007, certified by the Eco Mark Office of Japan Environment Association.

¹⁰ Applicable to HP Latex Inks. UL GREENGUARD GOLD Certification to UL 2818 demonstrates that products are certified to UL's GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit ul.com/gg or greenguard.org.

¹¹ EPEAT registered where applicable/supported. See epeat.net for registration status by country.

¹² Scratch-resistance comparison based on testing third-generation HP Latex Inks and representative hard-solvent inks. Estimates by HP Image Permanence Lab on a range of media.

¹³ HP image permanence estimates by HP Image Permanence Lab. Outdoor display permanence tested according to SAE J2527 on a range of media, including HP media; in a vertical display orientation in simulated nominal outdoor display conditions for select high and low climates, including exposure to direct sunlight and water; performance may vary as environmental conditions change. Laminated display permanence using HP Clear Gloss Cast Overlaminate, GBC clear gloss 1.7 mil hot laminate, or Neschen Solvoprint Performance Clear 80 laminate. Results may vary based on specific media performance.

¹⁴ For best results use media options intended for double-sided printing.

¹⁵ ICC profiling with the spectrophotometer does not support uncoated textiles and backlits.

¹⁶ The color variation inside a printed job has been measured at 10-pass mode on vinyl media within this limit: maximum color difference (95% of colors) <= 2 dE2000. Reflective measurements on a 943 color target under CIE standard illuminant D50, and according to the standard (IEDE2000 as per CIE Draft Standard DS 014-6/E-2012. 5% of colors may experience variations above 2 dE2000. Backlit substrates measured in transmission mode may yield different results.

¹⁷ Performance may vary depending on media—for more information, see hp.com/go/mediasolutionslocator. For best results, use textiles that do not stretch. The ink collector is required for porous textiles.

HP Latex 365 Printer



HP Custom Substrate Profiling

- Simplified color management, directly from the front panel, 8-inch touchscreen
- Pre-installed generic and HP substrate profile library
- Create custom ICC profiles with the i1 embedded spectrophotometer¹⁵




Spectrophotometer

- Color consistency for balanced production
- i1 embedded spectrophotometer enables automatic calibration¹⁵
- Delivers consistent colors to ≤ 2 dE2000¹⁶
- Color emulation workflow



Ink collector

- Expand into textile signage, no need to trim off margins
- Print on a wide variety of textiles—including porous textiles—with the ink collector¹⁷



NEW

Easy, remote online operator training

- Online self-help learning tools—from the basics on how to start operating the printer to tips such as how to grow your business with new applications

Visit: hp.com/communities/HPLatex300



NEW

HP Quick Solutions App

- Perform actions to optimize image quality
- Direct access from the front panel

HP Latex Technology

Technical specifications

Printing	Printing modes	91 m ² /hr (980 ft ² /hr) - Max Speed (1 pass) 31 m ² /hr (334 ft ² /hr) - Outdoor High Speed (4 pass) 23 m ² /hr (248 ft ² /hr) - Outdoor Plus (6 pass) 17 m ² /hr (183 ft ² /hr) - Indoor Quality (8 pass) 14 m ² /hr (151 ft ² /hr) - Indoor High Quality (10 pass) 6 m ² /hr (65 ft ² /hr) - Backlits, Textiles, and Canvas (16 pass) 5 m ² /hr (54 ft ² /hr) - High Saturation Textiles (20 pass)
	Print resolution	Up to 1200 x 1200 dpi
	Margins	5 x 5 x 0 x 0 mm (0.2 x 0.2 x 0 x 0 in) (without edge holders)
	Ink types	HP Latex Inks
	Ink cartridges	Black, cyan, light cyan, light magenta, magenta, yellow, HP Latex Optimizer
	Cartridge size	775 ml
	Printheads	6 (2 cyan/black, 2 magenta/yellow, 1 light cyan/light magenta, 1 HP Latex Optimizer)
	Color consistency ¹⁸	Average <= 1 dE2000, 95% of colors <= 2 dE2000
Media	Handling	Roll feed; take-up reel; automatic cutter (for vinyl, paper-based media, backlit polyester film)
	Media types	Banners, self-adhesive vinyls, films, fabrics, papers, wall-coverings, canvas, synthetics, mesh, textiles
	Roll size	254 to 1625-mm (10 to 64-in) rolls (580 to 1625-mm (23 to 64-in) rolls with full support)
	Roll weight	42 kg (92.6 lb)
	Roll diameter	250 mm (9.8 in)
Applications	Thickness	Up to 0.5 mm (19.7 mil)
	Banners, Displays, Double-sided banners, Exhibition and event graphics, Exterior signage, Indoor posters, Interior decoration, Light boxes – film, Light boxes – paper, Murals, POP/POS, Posters, Textile, Traffic signage, Vehicle graphics	
Connectivity	Interfaces (standard)	Gigabit Ethernet (1000Base-T)
Dimensions (w x d x h)	Printer	2561 x 840 x 1380 mm (101 x 33 x 54 in)
	Shipping	2795 x 760 x 1250 mm (110.1 x 30 x 49.3 in)
	Operating area	2761 x 1840 mm (109 x 72 in)
Weight	Printer	216 kg (476 lb)
	Shipping	303.5 kg (671.5 lb)
What's in the box	HP Latex 365 Printer, printheads, maintenance cartridge, ink collector, output platen protector, printer stand, spindle, take-up reel, variable front tension kit, loading accessory, user maintenance kit, edge holders, quick reference guide, setup poster, documentation software, power cords	
Environmental ranges	Operating temperature	15 to 30°C (59 to 86°F)
	Operating humidity	20 to 80% RH (non-condensing)
Acoustic	Sound pressure	55 dB(A) (printing); 39 dB(A) (ready); < 15 dB(A) (sleep)
	Sound power	7.4 B(A) (printing); 5.7 B(A) (ready); < 3.5 B(A) (sleep)
Power	Consumption	4.6 kW (printing); 85 watts (ready); < 2.5 watts (sleep)
	Requirements	Input voltage (auto ranging) 200 to 240 VAC (-10% +10%) two wires and PE; 50/60 Hz (+/- 3 Hz); two power cords; 16 A max per power cord
Certification	Safety	IEC 60950-1+A1+A2 compliant; USA and Canada (CSA listed); EU (LVD and EN 60950-1 compliant); Russia, Belarus, and Kazakhstan (EAC); Australia and New Zealand (RCM)
	Electromagnetic	Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia and New Zealand (RCM), Japan (VCCI)
	Environmental	ENERGY STAR, WEEE, RoHS (EU, China, Korea, India, Ukraine, Turkey), REACH, EPEAT Bronze, OSHA, CE marking compliant
Warranty	One-year limited hardware warranty	



3M™ MCS™ Warranty

Ordering information

Product	V8L39A	HP Latex 365 Printer
Accessories	FOM56A	HP Latex 64-in Printer 2-in Spindle
	FOM58A	HP Latex 64-in Printer 3-in Spindle
	FOM59A	HP Latex 300/500 User Maintenance Kit
	T7U74A	HP Latex 300/500 Ink Collector
Original HP printheads	CZ677A	HP 831 Cyan/Black Latex Printhead
	CZ678A	HP 831 Yellow/Magenta Latex Printhead
	CZ679A	HP 831 Light Magenta/Light Cyan Latex Printhead
	CZ680A	HP 831 Latex Optimizer Printhead
Original HP ink cartridges and maintenance supplies	CZ682A	HP 831A 775-ml Black Latex Ink Cartridge
	CZ683A	HP 831A 775-ml Cyan Latex Ink Cartridge
	CZ684A	HP 831A 775-ml Magenta Latex Ink Cartridge
	CZ685A	HP 831A 775-ml Yellow Latex Ink Cartridge
	CZ686A	HP 831A 775-ml Light Cyan Latex Ink Cartridge
	CZ687A	HP 831A 775-ml Light Magenta Latex Ink Cartridge
	CZ706A	HP 831 775-ml Latex Optimizer Ink Cartridge
	CZ681A	HP 831 Latex Maintenance Cartridge
Original HP large format printing materials	HP printing materials are designed together with HP Latex Inks and HP Latex printers to provide optimal image quality, consistency, and reliability.	
	HP Permanent Gloss Adhesive Vinyl REACH ¹⁹	
	HP Backlit Polyester Film ²⁰	
	HP PVC-free Durable Smooth Wall Paper REACH, ¹⁹ FSC® certified, ²¹	
	UL GREENGUARD GOLD Certified ²²	
Service and support	HP Premium Poster Paper ²⁰ FSC® certified ²¹	
	For the entire HP Large Format Printing Materials portfolio, please see HPLFMedia.com .	
	U9JE3E	HP 2 year Next Business Day with Defective Media Retention HW Support
	U9JE4E	HP 3 year Next Business Day with Defective Media Retention HW Support
	U9JE7PE	HP 1 year Post Warranty Next Business Day with Defective Media Retention HW Support
	U9JE8PE	HP 2 year Post Warranty Next Business Day with Defective Media Retention HW Support

¹⁸ The color variation inside a printed job has been measured to be within this limit: maximum color difference (95% of colors) <= 2 dE2000. Reflective measurements on a 943 color target under CIE standard illuminant D50, and according to the standard CIEDE2000 as per CIE Draft Standard D5014-6/E:2012. 5% of colors may experience variations above 2 dE2000. Backlit substrates measured in transmission mode may yield different results.

¹⁹ This product does not contain substances listed as SVHC (155) per Annex XIV of the EU REACH directive published as of June 16, 2014 in concentrations exceeding 0.1%. To determine the status of SVHC in HP products, see the HP REACH Declaration published at HP.Printing.Products.and.Consumable.Supplies.

²⁰ HP Large Format Media take-back program availability varies. Some recyclable HP papers can be recycled through commonly available recycling programs. Recycling programs may not exist in your area. See HPLFMedia.com/hp/ecosolutions for details.

²¹ BMG trademark license code FSC®-C115319, see fsc.org. HP trademark license code FSC®-C017543, see fsc.org. Not all FSC®-certified products are available in all regions.

²² UL GREENGUARD GOLD Certification to UL 2818 demonstrates that products are certified to UL's GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit ul.com/gg or greenguard.org.

